

价值源于可靠
Value in action

CRAWLER EXCAVATORS

履带式挖掘机



	Parameter	LG10E
▲ Main parameters	Operating weight	900kg
	Overall length	2200mm
	Overall width	930mm
	Overall height	2150mm
	Crawler belt length	1230mm
	Chasis width	930mm
	Standard bucket capacity	0.025m ³
▲ Main operationrange	Max. digging depth	1630mm
	Max. digging height	2750mm
	Max. dumping height	1960mm
	Max. digging radius	2900mm
	Min. rotation radius	1300mm
	Max. digging distance	2100mm
	Push blade lifting height	180mm
	Push blade fallinig depth	210mm
▲ Main performance specifications	Engine Type	Changchai192FAW/KoopKD192F (Euro V) UppowerKD192F(Euro V)
	Engine parameter	7.6kw-3000rpm /7kw-3000rpm/7.6kw-3000rpm
	Working pressure	16Mpa
	Main pump	6mL/r
	Gradeability	30°
	Max. digging force	10KN
	Operation mode	Mechanical operation

▶ **相关辅具 AVAILABLE ATTACHMENTS**



破碎锤 Breaking Hammer



旋挖钻 Rotary Drilling



松土器 Opener



快换 Quick Hitch



耙子 Rake



筛斗 Screening Bucket



倾斜斗 Tilting Bucket



抓木机 Wood Grapple

▶ **技术参数 TECHNICAL PARAMETER**

LG17E	LG18E	LG20E
1200kg	1855kg	2020kg
2460mm	3750mm	3550mm
1100mm	1050mm	1050mm
2270mm	2300mm	2370mm
1400mm	1620mm	1900mm
1100mm	1050mm	1050-1300mm
0.04m ³	0.05m ³	0.05m ³
2000mm	2200mm	2200mm
3000mm	3660mm	3600mm
2050mm	2520mm	2500mm
3500mm	3770mm	3800mm
1600mm	1500mm	1700mm
2700mm	2660mm	2500mm
180mm	320mm	230mm
200mm	200mm	160mm
Laidong380	ChangchaiZN390Q/Laidong KM385B Xinchai3B11X40(Euro V)	Yanmar3TNV70/KubotaD902(Euro V) EPA
19KW/2200rpm	18Kw-2200rpm/18.1kw-2200rpm/18.5kw-3000rpm	10kw-2200rpm/12kw-2300rpm
18MPa	18Mpa	20Mpa
10+4ml/r	9+9+3ml/r	18ml/r
30°	35°	35°
11KN	12KN	12KN
Pilot hydraulic control	Pilot hydraulic control	Pilot hydraulic control