

价值源于可靠
Value in action



▶ 技术参数 TECHNICAL PARAMETER

Model	LG15F	LG35F	LG35F
Load Capacity	1500kg	3500kg	
Engine	Yunnei 490/42KW	Yunnei 490/42KW	
Axle	130 bridge weighted steel bridge	Small wheel side weighted cast steel bridge	Small whe
Tyres	Semi-solid 10.00-16	Steel wire tire 20.5/70-16	
Gearbox	265 gearbox	265 double high low speed gearbox	265 doub
Min.turning radius	4600mm	4700mm	
Mast width	148mm	160mm	
Lift height	3000mm	3000mm	
Full-load maximum gradeability	<35°	<35°	
Fork size	1220mm	1220mm	
Frame articulation	Front 200mm, rear 150mm	Front 300mm, rear 250mm	Front
Driving type	Four-wheel drive	Four-wheel drive	
Minimum ground clearance	250mm	250mm	
Front tilt angle	14°	14°	
Mast height	2220mm	2240mm	
Dimension	3100/1300/2300mm	4160/1850/2500mm	

ALL-TERRAIN FORKLIFTS

全地形叉车



▶ 相关辅具 AVAILABLE ATTACHMENTS



铲斗 Bucket




加上抓 Upper Clip



直板抱夹 PSC

▶ 产品细节 PRODUCT DETAILS



WIDE FIELE OF VIEW	LG45F	LG55F
3500kg	4500kg	5500kg
Yunnei 490/42KW	Yunnei 4100/65KW	Yunnei 4102/76KW
el side weighted cast steel bridge	Middle wheel side weighted cast steel bridge	Big wheel side weighted cast steel bridge
Steel wire tire 20.5/70-16	Steel wire tire 16/70-20	Steel wire tire 16/70-24
le high low speed gearbox	280 double high low speed gearbox	280 double high low speed gearbox
4700mm	4800mm	4800mm
160mm	180mm	180mm
3000mm	3000mm	3000mm
<35°	<35°	<35°
1220mm	1220mm	1220mm
300mm, rear250mm	Front 400mm, rear300mm	Front 500mm, rear300mm
Four-wheel drive	Four-wheel drive	Four-wheel drive
250mm	300mm	300mm
14°	14°	14°
2240mm	2790mm	2790mm
4030/1800/2300mm	4150/1945/2450mm	4150/1945/2450mm